



Pearl

Pearl comes with slim, elegant and compact design. Durable die-casting aluminum housing with PC lens makes it dirt and water-proof, IP66 and IK10 rated. Full cut-off asymmetric optic design for well light control to obtain 0% upward light, which meets with high standard request in the market. Lumen efficacy up to 135lm/W @ 4000K Ra80.

EN

- Corrosion resistant die cast aluminium alloy.
- Installation with bracket on walls.
- Mains voltage: 220-240V / 50-60Hz.
- Asymmetric beam angle available.
- Led colour temperatures are optionally 2700K, 3000K, 3500K, 4000K, 5000K and 6500K.
- Weatherproof and durable silicone rubber gasket.
- Ultraviolet stabilized polyester powder coat finish in white, black, dark gray and light gray finish.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- All external screws are stainless steel.
- High colour consistency: <3 SDCM
- L80 B10 50000hrs and five years warranty.

TR

- Korozyona dayanıklı alüminyum gövde.
- Duvara braketli montaj sistemine sahiptir.
- 220-240V / 50-60Hz enerji giriřli.
- Asimetrik optik yapılı.
- 2700K, 3000K, 3500K, 4000K, 5000K ve 6500K renk sıcaklıęı seçenekleri mevcuttur.
- Su geçirmezlięi saęlayan silikon conta.
- Ultraviyole ışımaya dayanıklı beyaz, açık gri, antrasit gri ve siyah elektrostatik toz boyalı.
- Çift katmanlı polyester toz boya sayesinde korozyona ve tuza dayanıklı gövde.
- Tüm dış civatalar paslanmaz çelik.
- Yüksek LED renk uyumu: <3 SDCM
- L80 B10 50000 saat ve beř yıl garanti.

Pearl



5 / Product Color / Ürün Renk



White = 01





Light Gray = 04






Textured Metallic
Dark Gray = 05



Black = 03



Technical Drawing / Teknik Çizim



Pearl / O07.WA.06100



Power / Güç	CRI	Order Code / Sipariş Kodu	Kelvin	Lümen T _c =50° Lümen
38W	CRI>80	O07.WL.06100 . (..) . (..) . (..) . (..)	2700K	4715
			3000K	4866
			3500K	4941
			4000K	5130
			5000K	5205
			6500K	5360

* Code example / Kod örneği:

O07.WA.06100 . 38 . 827 . ASM . 01

1- Product code / Armatür kodu

2- Power / Güç

3- CRI / Kelvin

4- Reflector angle / Reflektör açısı

5- Colour / Ürün renk

Complete Code / Komple Kod	2	3	4	5
	Watt - Driving Current / Watt - Sürüş Akımı	CRI / Kelvin	Reflector Angle / Reflektör Açısı	Product Color / Ürün Renk
(..) / Complete Code / Komple Kod	38 38W	827 CRI>80 - 2700K	ASM Asymmetric	01 white
	23 23W	830 CRI>80 - 3000K		02 ral 9010
	14 14W	835 CRI>80 - 3500K		03 black
		840 CRI>80 - 4000K		04 gray
		850 CRI>80 - 5000K		05 dark gray
		865 CRI>80 - 6500K		06 special color